

INSTALLATION GUIDE



6252 BUCKET SEAT SET

Chevrolet Express (2016-2018)

GMC Savana (2016-2018)

BILL OF MATERIALS

Item No.	Description	Qty.
62-523	Seat Back Cover Passenger Side	1
62-521	Seat Bottom Cover Passenger Side	1
62-522	Seat Back Cover Driver Side	1
62-523	Seat Bottom Cover Driver Side	1

QUICK START GUIDE

Phase 1 - Preparation

- ❑ 1.1 Adjust seat.

Phase 2 - Installation

- ❑ 2.1 Install Seat Back Cover.
- ❑ 2.2 Install Seat Bottom Cover.

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.
Drip dry or machine tumble dry on a no heat cycle.
Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

PHASE 1 – PREPARATION

1.1 REMOVING

- ❑ 1.1 Adjust Seat
 - ❑ Lean seat back forward and slide seat ahead.

PHASE 2 – INSTALLATION

2.1 SEAT COVER INSTALLATION



- ❑ 2.1 Install Seat Back Cover.
 - ❑ Ensure the tag inside the cover corresponds with the seat you are working on. Each cover will have a Driver or Passenger tag.
 - ❑ Turn seat cover 3/4 of the way inside out.
 - ❑ Pull seat back cover into position.
 - ❑ Continue pulling the cover down the seat back, turning it right side out as you go.
 - ❑ Push flap from front of cover between seat back and seat bottom, out the back of the seat .
 - ❑ Double the end of the flap over to prevent the “hook” Velcro from sticking to the factory upholstery.
 - ❑ Pull the flap tight and attach to the Velcro on the back of the seat.
 - ❑ Fasten flap under the armrest.

❑ 2.2 Install Seat Bottom Cover.



- ❑ Ensure the tag inside the cover corresponds with the seat you are working on. Each cover will have a Driver or Passenger tag.
- ❑ Place seat bottom cover over bottom of seat.



- ❑ Push flap on top of cover between seat back and seat bottom.
- ❑ Velcro side flaps to factory upholstery on rear of seat bottom.
- ❑ Pull strings tight.
- ❑ Tie a loop in one string, close to the edge of the seat.
- ❑ Run the other string through the loop and pull as tight as possible. This is what keeps your seat bottom from shifting.



UNDER



Seat cover bottom flap, running OVER all bars, wires, etc.

- ❑ Pull bottom flaps from front of seat bottom and attach to top flap.
- ❑ Flaps **MUST** run OVER bars and brackets under seat.



“Congratulations, you have successfully installed your
Seat Cover Set!

Thank you for doing business with us.”

